


B19

B19 is a hybrid moving head stage light with beam, wash and kaleido effects. Its zoomable range from 4° to 60°, from narrow beam to wide wash effect. The fixture is designed for for concerts, TV shows, auto shows, theatre, sport venues.

Key Features:

- 19 x 15Watt RGBW LED source
- Individual control of each LEDs, unique honeycomb designed lens
- Rotating front lens without limitation for vortex effects
- Operating modes: wash, beam, FX effects
- Motorized zoom range from 4° - 60°
- Accurate positioning
- LCD display, user friendly operation menu
- DMX512, auto program, sound control
- Display reverse 180°
- Powercon in & out connection



PHYSICAL

Length: 415 mm (16.3 in.)
Width: 275 mm (10.8 in.)
Height: 425 mm (16.7 in.)
Net Weight: 15 kg (33 lb.)

DYNAMIC EFFECTS

Color mixing: RGBW
Zoom: motorized zoom
Individual control of each LEDs
Pan: 540°
Tilt: 270°
Electronic dimming: 0 – 100%
Strobe and pulse effects: Variable speed and action, random strobe

CONTROL AND PROGRAMMING

Control options: DMX, auto, sound, master-slave
DMX channels: 21/23/35/78/92/97/99
DMX address setting: Control panel with LCD display
DMX compliance: USITT DMX512-A

OPTICS

Light source: 19 x 15Watt LEDs
Color temperature: adjustable
Zoom: 4° - 60° motorized zoom
LED lifetime: 50,000 hours avg.*

*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming

CONSTRUCTION

Housing: Engineering grade plastic
Color: Black
Environment: IP20 indoor use

INSTALLATION

Mounting: 2 x Omega brackets

Location: Dry location only, must be fastened to surface or structure

Orientation: Any

Minimum distance to combustible materials: 0.3 m (1.0 ft.)

Minimum distance to illuminated surfaces: 3 m (9.8 ft.)

CONNECTIONS

AC power in, thru: PowerCon in & out
DMX data in/thru: 3-Pin XLR in & out(5-Pin optional)

ELECTRICAL

AC power: 100–240 V nominal, 50/60 Hz
Power supply unit: Auto ranging power unit

TYPICAL POWER AND CURRENT

230 V, 50 Hz: 285 Watt max.
Allow for a deviation of +/- 10%.

THERMAL

Cooling: Forced air
Maximum ambient temperature (Ta max.): 40° C (104° F)
Minimum ambient temperature (Ta min.): 5° C (41° F)

SHIPPING INFORMATION

In carton:

Carton dimensions: 470 x 370 x 510 mm (18.5 x 14.6 x 30 in.)

Gross weight: 19 kg (41.8 lbs.)

In flightcase(2-way):

Case dimensions: 940 x 440 x 710 mm (37 x 17.3 x 27.9 in.)

Gross weight: 60 kg (132.2 lbs.)