POP 1018

Ovation
-by Hotion

POP 1018 is a LED par light powered by 18 x 10Watt LED source. Features RGBWA+UV 6 in 1 color mixing(brings almost endless colors), electronic strobe, 0 - 100% dimming. The double yoke stand makes it possible for both truss or floor installation.

Key Features:

- 18 x 10W high power LED
- · RGBWA+UV 6 in 1 color mixing
- · Various built-in color marcos
- · DMX, auto, sound control
- Electronic strobe
- Video flcker free


PAR LIGHT

- Master-slave operation
- Aluminum housing
- · RGBW or RGBWA version selectable









Electrical

Power supply: Electronic auto-ranging Input voltage range: AC100-240V, 50/60Hz

Source

Light source: 18 x 10W 6-in-1 LEDs Color temperature: RGBWA-UV LED lifetime: 50,000 hours avg.*

*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

Effects

Dimming: 0 - 100% continuous dimming
Electronic Strobe

Color and Chase Macros

Beam angle: 25°

Control and Programming

Control mode: DMX, Auto program, Sound

activate, Master-slave DMX channels: 6/10

Addressing and setting: Control panel with

digital display and control buttons

Connection

Power connection: Power cable in Signal connection: 3-pin XLR in & out

Construction

Housing: die-cast aluminium

Colour. Black Enviroment: IP20

Thermal

Cooling: Forced ventilation with fans Maximum ambient temperature: 40° C (104° F) Minimum ambient temperature: 5° C (41° F)

Physical

Size: 280 x 215 x 310mm(11 x 8.5 x 12.2in) Package size: 250 x 250 x 360mm(9.8 x 9.8 x

14.2in)

N.W.: 2.3kg(5.1lb)

Accessories

Included: Power cable, Manual Optional: Safety cable, Clamp

*Also available in RGBW or RGBWA version

Photometric Data

Distance(m)	2	3	4	5	6	7	8	9	10
			- 1				1	- 1	
				- 1			- 1	- 1	
	- 1	- 1		1			- 1	- 1	
	1			1			1		
	1			- 1			- 1		
		- ;		-	- ;	- ;	- 1	- ;	
Full on	4660	2400	1240	888	618	457	360	271	22
Lux - UV	/	/	/	/	/	/	/	/	/
Lux - A	381	186	110	66	47	33	25	18	1
Lux - W	2150	1070	561	366	251	184	137	106	8
Lux - B	224	116	66	41	28	21	17	12	ç
Lux - G	1690	902	516	343	244	179	135	109	8
Lux - R	800	354	194	121	89	61	53	36	3