

PRODUCTS

Hotion®

QUICK GUIDE



Theatrical & studio

Art gallery lights

Architectural lights

Professional stage

www.hotion.com

VOL.5



Reborn 200

- S4 LED retrofit single white
- HPL 575 equivalent
- 3200K, 4000K, 5600K opt.
- High CRI, TLCI, CQS
- 100 - 240V support
- XLR signal connection
- Easy to setup and install

New



Reborn 200T

- S4 LED retrofit tunable white
- HPL 575 equivalent
- 2200K - 7000K dual white CCT
- High CRI, TLCI, CQS
- 100 - 240V support
- XLR signal connection
- Easy to setup and install

New



UHD 60

- 40W LED shapeable light
- 5600K color temperature
- Four shutters control light shape
- High CRI of 92
- 60° fixed lens, UHD optics
- No lens distortion
- DMX, RDM control



Mini Leko 20

- 20W LED profile spot
- 3200K or 5600K color temp
- High CRI of 92
- Aluminum housing, fan-free
- 19°, 26°, 36°, 50° lens opt.
- DMX control
- Black or white body

New



Panto Leko 60

- 60W LED profile zoom IP65
- 2700K - 6000K dual white CCT
- Zoom 15° - 30°, 25° - 50° opt.
- DMX, RDM control
- High CRI ≥ 92
- IP 65 rated, outdoor available
- E-sized gobo holder

New



Art 50 Spot

- 40W LED profile spot zoom
- 2700K - 6000K CCT
- 15° - 30° manual zoom
- High CRI over 92
- Four shutters control light shape
- black or white body
- DMX, RDM support



S20T

- 20W tunable LED profile spot
- 2700K - 6000K CCT
- High CRI over 92
- Aluminum housing, fan-free
- 19°, 26°, 36°, 50° lens opt.
- DMX control
- Black or white body



X40

- 40W LED profile spot
- 3200K or 5600K color temp
- High CRI of 92
- Aluminum housing, fan-free
- 19°, 26°, 36°, 50° lens opt.
- E-sized gobo holder
- Black or white body



Scan for details

X40T

- 40W tunable LED profile spot
- 2700K - 6000K CCT
- High CRI of 92
- Aluminum housing, fan-free
- 19°, 26°, 36°, 50° lens opt.
- Eszied gobo holder
- Black or white body

COB 40W LED	2700K - 6000K
92 CRI	Flicker Free
RDM	Fan-free



Scan for details



Scan for video

Mini Profile 40Z

- 40W LED profile spot zoom
- 3200K, 4000K, 5600K opt.
- High CRI of 92
- Aluminum housing, fan-free
- 15° - 30° manual zoom lens
- Black or white body
- Track mount version opt.

COB 40W LED	DMX DMX control
92 CRI	Flicker Free
RDM	Fan-free



Scan for details

Honor 250C Zoom

- 250W RGBW LED profile spot
- RGBW color mixing
- 18° - 38° manual zoom
- 3000K - 8000K CCT
- Dimmer frequency
- Dimmer curves
- Smart fan, silent

COB 250W LED	RGBW LED
Flicker Free	Zoom
RDM	Silent



Scan for details



Scan for video

Honor 300 Zoom

- 300W white LED profile spot
- 3200K or 5600K opt.
- 18° - 38° manual zoom
- 1KW tungsten equivalent
- High CRI 97, TLCI 98
- Dimmer curves, frequency
- Smart fan, silent

COB 300W LED	98 TLCI
Flicker Free	Zoom
RDM	Silent



Scan for details

S40T

- 40W LED profile spot zoom
- 2700K - 6000K CCT
- High CRI of 92
- Aluminum housing, fan-free
- 15° - 30° manual zoom lens
- Black or white body
- Track mount version opt.

COB 40W LED	2700K - 6000K
92 CRI	Flicker Free
RDM	Fan-free



Scan for details

Honor 200 Zoom

- 200W white LED profile spot
- 3200K or 5600K opt.
- 18° - 38° manual zoom
- Bright output
- High CRI 97, TLCI 98
- Dimmer curves, frequency
- Smart fan, silent

COB 200W LED	98 TLCI
Flicker Free	Zoom
RDM	Silent



New



Scan for details

CTC 300 Profile

- 300W dual white LED profile
- 2800K - 6500K CCT
- 18° - 38° manual zoom
- HD optics
- High CRI 96, TLCI 98
- Dimmer curves, frequency
- Smart fan, silent operation

COB 300W LED	2800K - 6500K
Flicker Free	Zoom
RDM	Silent



Scan for details

Honor 350C Zoom


- 350W RGBALC LED profile
- RGBALC color mixing
- High CRI 95, TLCI 98
- 18° - 38° manual zoom
- 2700K - 8000K CCT
- Dimmer curves, frequency
- Smart fan, silent

COB 350W LED	RGBALC
Flicker Free	Zoom
RDM	Silent




Profile S250C

- o 250W RGBW LED profile spot
- o RGBW color mixing
- o 19°, 26°, 36°, 50° lens opt.
- o 3000K - 8000K CCT
- o Dimmer frequency
- o Dimmer curves
- o Smart fan, silent




Profile S300

- o 300W white LED profile spot
- o 3200K or 5600K opt.
- o 19°, 26°, 36°, 50° lens opt.
- o 1KW tungsten equivalent
- o High CRI 97, TLCI 98
- o Dimmer curves, frequency
- o Smart fan, silent




Mini Fresnel 40Z

- o 40W LED fresnel single white
- o CRI 95, R9≥90, TLCI 98
- o 25° - 80° manual zoom
- o Smooth dimming, flicker free
- o Super compact, easy for set up
- o Rotary, key, DMX control
- o 4-leaf rotatable barndoor




Mini Fresnel 50T

- o 50W LED fresnel tunable white
- o 2700K - 6500K CCT
- o CRI 95, R9≥90, TLCI 98
- o 25° - 80° manual zoom
- o Super compact, easy for set up
- o Rotary, key, DMX control
- o 4-leaf rotatable barndoor




Profile S300T

- o 300W dual white LED profile
- o 2800K - 6500K CCT
- o 19°, 26°, 36°, 50° lens opt.
- o HD optics
- o High CRI 96, TLCI 98
- o Dimmer curves, frequency
- o Smart fan, silent operation




Profile S350C

- o 350W RGBALC LED profile
- o RGBALC color mixing
- o High CRI 95, TLCI 98
- o 19°, 26°, 36°, 50° lens opt.
- o 2700K - 8000K CCT
- o Dimmer curves, frequency
- o Smart fan, silent



Mini Fresnel 40C


- o 40W LED fresnel zoom
- o RGBW color mixing
- o 40Watt for each color
- o 25° - 80° manual zoom
- o Super compact, easy for set up
- o Rotary, key, DMX control
- o 4-leaf rotatable barndoor



New

Art 50 Wash

- o 40W LED fresnel zoom
- o 2700K - 6000K CCT
- o 10° - 60° manual zoom
- o High CRI over 92
- o Aluminum housing
- o black or white body
- o DMX, RDM support



New



Scan for details



Scan for video

Event 100T

- 100Watt tunable white fresnel
- 2700K - 6000K CCT
- 25° - 65° manual zoom
- Average CRI 95, TLCI 97
- Super compact size
- Barndoor included
- Rotary control dimmer, CCT

2700K - 6000K	97 TLCI
	95 CRI

New



Scan for details



Scan for video

Event 200T

- 200Watt tunable white fresnel
- 2700K - 6000K CCT
- 25° - 65° manual zoom
- Average CRI 95, TLCI 97
- Super compact size
- Barndoor included
- Rotary control dimmer, CCT

2700K - 6000K	97 TLCI
	95 CRI



Scan for details



Pioneer 100T Zoom

- 100W LED fresnel tunable white
- 2700K - 6000K CCT
- Soft and even wash effect
- High CRI 95, TLCI 97
- Soft and even wash effect
- 25° - 65° motorized zoom
- Video flicker free

100W LED	2700K - 6000K



Scan for details



Pioneer 200 Zoom

- 200W LED fresnel single white
- 3200K or 5600K CCT
- CRI 97, R9≥90, TLCI 98
- 15° - 60° motorized zoom
- Smooth dimming, flicker free
- DMX, RDM control
- Barndoor included

200W LED	
	97 CRI



Scan for details



Pioneer 100 Zoom

- 100W LED fresnel single white
- 3200K or 5600K CCT
- CRI 97, R9≥90, TLCI 98
- 25° - 65° motorized zoom
- Smooth dimming, flicker free
- DMX, RDM control
- Barndoor included

100W LED	
	97 CRI



Scan for details



Pioneer 100C Zoom

- 100W LED fresnel RGBW
- RGBW color mixing
- Soft and even wash effect
- 25° - 65° motorized zoom
- Smooth dimming, flicker free
- DMX, RDM control
- Barndoor included

100W LED	



Scan for details



Pioneer 200C Zoom

- 200W LED fresnel RGBW
- RGBW color mixing
- Soft and even wash effect
- 15° - 60° motorized zoom
- Smooth dimming, flicker free
- DMX, RDM control
- Barndoor included

200W LED	



Scan for details



Pioneer 200T Pro

- 200W LED fresnel tunable white
- Smaller but brighter than Pioneer 200
- 2700K - 6500K CCT
- Average CRI 97, TLCI 98
- Soft and even wash effect
- 10 - 55° motorized zoom

200W LED	2700K - 6000K
	97 CRI




Pioneer 200C Pro

- 200W LED fresnel RGBALC
- RGBALC color mixing
- Soft and even wash effect
- CRI≥95(CT channel), 85(full on)
- Soft and even wash effect
- 10 - 55° motorized zoom
- Video flicker free



Pioneer 300 Zoom

- 300W LED fresnel single white
- 3200K or 5600K CCT
- CRI 97, R9≥90, TLCI 98
- 8° - 60° motorized zoom
- 3 + 5pin DMX, RDM support
- Super bright output
- Barndoor included



Solar Panel 150T

- 150Watt LED studio panel
- 3200K - 5600K dual white CCT
- Super bright, uniform coverage
- Super silent operation
- High CRI 98, TLCI 98
- Rotary, DMX, RDM control
- 8 - leaf barn door



Solar Panel 200

- 200Watt LED studio panel
- 3200K or 5600K color temp
- Super bright, uniform coverage
- Super silent operation
- High CRI 95, TLCI 98
- Rotary, DMX, RDM control
- 8 - leaf barn door




CTC 300 Fresnel

- 300W LED fresnel tunable white
- 2800K - 6500K CCT
- Soft and even wash effect
- High CRI 98, TLCI 98
- Soft and even wash effect
- 8° - 60° motorized zoom
- Video flicker free



Pioneer 350C Zoom

- 350W LED fresnel RGBALC
- RGBALC color mixing
- Soft and even wash effect
- High CRI 95, TLCI 98
- Soft and even wash effect
- 20 - 55° motorized zoom
- Video flicker free



Solar Panel 300T

- 300Watt LED studio panel
- 3200K - 5600K dual white CCT
- Super bright, uniform coverage
- Super silent operation
- High CRI 98, TLCI 98
- Rotary, DMX, RDM control
- 8 - leaf barn door



New



Solar Panel 300C

- 300W LED studio panel RGBWW
- 2800K - 8000K CCT
- Super bright, uniform coverage
- Turbo mode available for brighter
- High CRI 95, TLCI 98
- Rotary, DMX, RDM control
- 8 - leaf barn door



Solar CYC

- 175Watt LED cyclorama
- 3200K or 5600K color temp
- Super bright, uniform coverage
- CRI 98, R9≥93, TLCI 98
- Flicker free operation
- PWM 1.2 - 20 KHz
- Super silent operation

LED technology	98 CRI
Flicker Free	98 TLCI
RDM	Silent



CYC RGBW

- 175Watt LED cyclorama
- RGBW color mixing
- Super bright, uniform coverage
- DMX RDM protocols
- Flicker free operation
- PWM 1.2 - 20 KHz
- Super silent operation

RGBW LED	PowerCon
Flicker Free	2.7 Compact
RDM	Silent

New



Chinlite 5600

- LED chin light
- 5600K color temperature
- High CRI, TLCI, CQS
- Beehive diffuser available
- 0 - 100% smooth dimming
- 1 controller control 4 lights
- DMX, manual control



Par Master X1

- 150Watt LED fresnel zoom par
- 3200K or 5600K color temp.
- CRI 96, TLCI 98
- 25° - 80° manual zoom
- Smooth dimming, flicker free
- DMX, RDM control
- Rotating barndoor included

COB 150W LED	Zoom
Flicker Free	96 CRI
RDM	98 TLCI

New



Atmos 100T

- 100W dual white down light
- 2700K - 6900K CCT
- High bright, uniform coverage
- Fan-free design
- High CRI 96, TLCI 98
- Dimmer curves selectable
- Smooth dimming, flicker free

COB 100W LED	98 TLCI
Flicker Free	96 CRI
RDM	Fan-free

New



Atmos 100C

- 100W RGBW down light
- RGBW color mixing
- High bright, uniform coverage
- Fan-free design
- Aluminum housing
- Dimmer curves selectable
- Smooth dimming, flicker free

COB 100W LED	RGBW LED
Flicker Free	PowerCon
RDM	Fan-free



Par Master C1

- 150Watt LED fresnel zoom par
- RGBW color mixing
- Flat and even color mixing
- 25° - 80° manual zoom
- Smooth dimming, flicker free
- DMX, RDM control
- Rotating barndoor included

COB 150W LED	RGBW LED
Flicker Free	Zoom
RDM	



Blinder 400

- 4 x 100W LED, high brightness
- Individual control of each LED
- 3200K - 5600K tunable, single white optional
- Smooth dimming, flicker free
- Aluminum housing

New



Scan for details

Showgun 10

- 10W LED track spot light
- 2700K - 6000K CCT
- High CRI of 96
- Aluminum housing, fan-free
- 10° - 60° manual zoom
- 4 wire track adapter
- Black or white body

COB 10W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun 20

- 20W LED track spot light
- 2700K - 6000K CCT
- High CRI of 96
- Aluminum housing, fan-free
- 10° - 60° manual zoom
- 4 wire track adapter
- Black or white body

COB 20W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun Spot 20S

- 20W LED track framing light
- 2700K - 6000K CCT
- High CRI of 96
- 4 shutters control light shape
- 25° fixed lens
- 4 wire track adapter
- Black or white body

COB 20W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun Spot 20

- 20W LED track framing light
- 2700K - 6000K CCT
- High CRI of 96
- 4 shutters control light shape
- 30° fixed lens
- 4 wire track adapter
- Black or white body

COB 20W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun 35

- 35W LED track spot light
- 2700K - 6000K CCT
- High CRI of 96
- Aluminum housing, fan-free
- 10° - 60° manual zoom
- 4 wire track adapter
- Black or white body

COB 35W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun Spot 10

- 10W LED track framing light
- 2700K - 6000K CCT
- High CRI of 96
- 4 shutters control light shape
- 25° fixed lens
- 4 wire track adapter
- Black or white body

COB 10W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun Spot 35

- 35W LED track framing light
- 2700K - 6000K CCT
- High CRI of 96
- 4 shutters control light shape
- 30° fixed lens
- 4 wire track adapter
- Black or white body

COB 35W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun Spot 35 Zoom

- 35W LED track framing light
- 2700K - 6000K CCT
- High CRI of 96
- 4 shutters control light shape
- 15° - 25° / 25° - 50° manual zoom
- 4 wire track adapter
- Black or white body

COB 35W LED	2700K - 6000K
96 CRI	Flicker Free
Track 3 circuits	Fan-free

New



Scan for details

Showgun Spot 20F

- 20W LED track framing light
- 2700K - 6000K CCT
- High CRI of 96
- 4 shutters control light shape
- 19°, 26°, 36°, 50° lens optional
- 4 wire track adapter
- Black or white body

COB 20W LED	2700K - 6000K
Flicker Free	96 CRI
Fan-free	Track 3 circuits



Scan for details

Spacegun 10

- 10W LED track spot light
- 2700K - 6000K CCT
- High CRI of 96
- Aluminum housing, fan-free
- 10° - 60° manual zoom
- 4 wire track adapter
- Black or white body

COB 10W LED	2700K - 6000K
Flicker Free	96 CRI
Fan-free	Track 3 circuits



Scan for details

UHD 200

- 200W dual white LED profile
- 2800K - 6500K CCT
- 30° or 60° fixed lens
- UHD optics, no lens distortion
- Gobo holder available
- Dimmer curves, frequency
- IP20 rated

COB 200W LED	2800K - 6500K
Flicker Free	Silent
RDM	



Scan for details

UHD 300

- 300W dual white LED profile
- 2800K - 6500K CCT
- 30° or 60° fixed lens
- UHD optics, no lens distortion
- Gobo holder available
- Dimmer curves, frequency
- IP20 rated

COB 300W LED	2800K - 6500K
Flicker Free	Silent
RDM	



Scan for details

Spacegun 20

- 20W LED track spot light
- 2700K - 6000K CCT
- High CRI of 96
- Aluminum housing, fan-free
- 10° - 60° manual zoom
- 4 wire track adapter
- Black or white body

COB 20W LED	2700K - 6000K
Flicker Free	96 CRI
Fan-free	Track 3 circuits



Scan for details

Spacegun 35

- 35W LED track spot light
- 2700K - 6000K CCT
- High CRI of 96
- Aluminum housing, fan-free
- 10° - 60° manual zoom
- 4 wire track adapter
- Black or white body

COB 35W LED	2700K - 6000K
Flicker Free	96 CRI
Fan-free	Track 3 circuits

New



Scan for details

Panto Leko 300

- 300W dual white LED profile IP
- 2800K - 6500K CCT
- 30° or 60° fixed lens
- UHD optics, no lens distortion
- Gobo holder available
- Dimmer curves, frequency
- IP65 rated, outdoor use

COB 300W LED	2800K - 6500K
Flicker Free	IP65
RDM	Silent



Scan for details



Scan for video

Hero 300 Super Beam

- o 80W LED moving head beam
- o Super bright optical system
- o 2 degree beam angle
- o 1 Color wheel with 10 colors+open
- o 1 Gobo wheel with 13 fixed gobo+open
- o 1 effect color wheel



Scan for details



Scan for video

Hero 300 Spot

- o 200W LED moving head spot
- o 7° - 20° motorized zoom
- o 1 Color wheel with 9 colors + open
- o 1 Gobo wheel with 9 fixed gobo + open
- o 1 Gobo wheel with 7 rotating gobo + open
- o 3 facet circular rotating indexable prism



Scan for details

Hero 400 Framing

- o 400Watt LED moving head framing
- o 6000K LED
- o CRI, TLCI up to 95
- o 1 color wheel with 6 colors + CTO
- o Auto framing
- o Motorized zoom
- o Double frost effect (Heavy frost + light frost)



Scan for details

Hero 700 Framing

- o 700Watt LED moving head framing
- o 1 rotating gobo wheel with 7 rotating gobos
- o 1 fixed gobo wheel with 15 gobos, variable speed jitter/bidirectional rotation
- o 1 dynamic fire plate, reversible and 360 degree infinite rotation
- o 5.5° - 50° linear high-speed zoom



Scan for details



Scan for video

Hero 300 Performance

- o 300W LED moving head performance
- o Spot, Wash, Animation effect all-in-one
- o 1 Animation wheel, 3 - facet prism
- o 1 Color wheel with 7 colors + open
- o 1 Gobo wheel with 8 fixed gobo + open
- o 1 Gobo wheel with 7 rotating gobo + open



Scan for details

Hero 400 BSW

- o 400W LED moving head Beam Sport Wash
- o 4° - 35° motorized zoom (spot mode)
- o 1 color wheel with 8 colors
- o 1 static gobo wheel with 12 gobos
- o 1 rotating gobo wheel with 7 gobos
- o 1 animation wheel
- o CMY + CTO...



Scan for details



Scan for video

Mainforce 740

- o 7 x 40W RGBW LED moving head beam wash
- o 5° - 50° motorized zoom
- o Accurate positioning, auto correction
- o Compact body, light weight
- o PowerCon in & out connection
- o Available in pixel and non pixel control



Scan for details



Scan for video

Mainforce 1240

- o 12 x 40W RGBW LED moving head beam wash
- o Color macros function
- o LED rainbow effect
- o Strong beam effect, flat and nice wash effect
- o Individual control of each LED
- o 8° - 50° motorized zoom
- o Super fast head moving



Scan for details

C19

- 19 x 15Watt RGBW LED beam wash
- Flat and even RGBW color mixing
- Motorized zoom 8° - 50°
- DMX, Auto, Master-slave, Sound control
- Pan 540°, Tilt 270°, accurate positioning
- Rapid pan & tilt movement
- 10/15/21/37 DMX channels



Scan for details

B19

- 19 x 15Watt LED beam, wash and kaleido effects
- Individual control of each LEDs, honeycomb designed lens
- Rotating front lens without limitation for vortex effects
- Operating modes: wash, beam, FX effects
- Motorized zoom range from 4° - 60°
- Powercon in & out connection



Scan for details

POP 1018

- 18 x 10W LED par light
- RGBWA+UV 6 in 1 color mixing
- Various built-in color marcos
- DMX, auto, sound control
- Master-slave operation
- Aluminum housing
- RGBW or RGBWA version selectable



Scan for details

POP 354

- 54 x 3W LED par light
- RGBW(12R, 18G, 18B, 6W) LED
- Master-slave operation
- Aluminum housing
- Overheat protection
- IP 20 indoor use
- Built-in color marcos



Scan for details

Mainforce 1940

- 19 x 40W LED moving beam wash
- RGBW 4in1 color mixing
- Individual control of each LEDs
- 4° - 60° moto zoom
- Rotating front lens without limitation for vortex effects
- Operating modes: wash, beam, FX effects



Scan for details

P19

- 19 x 15W LED zoom par
- RGBW LED color mixing
- Motorized zoom from 15° - 60°
- 3 separate LED zones controllable
- Auto, master-slave, sound activate
- 5/10/16/32 DMX channels
- Powercon in & out connection



Scan for details

EXT 1218

- 18 x 12W LED par IP rated
- RGBW 4in1 color mixing
- Master-slave operation
- 25°, 45° lens optional
- Overheat protection
- Built-in color marcos
- IP65 rated, outdoor use



Scan for details

P740 (EXT 740)

- 7 x 40W RGBW LED zoom par IP rated
- High efficient optical lens
- Strong beam effect, flat and nice wash effect
- 5° - 45° motorized zoom range
- IP rated powerCon in & out connectors
- Die-casting aluminium body, compact design
- IP 65 rated, outdoor use



Scan for details

Batt Par Q6

- o 6pcs RGBWA-UV LED battery par
- o Compact, easy for set up
- o Onboard 2.4G wireless DMX
- o App available in IOS and Android phone
- o IR control available
- o Rechargeable, Li-ion battery powered
- o Black and white housing selectable



Scan for details

Power par 350

- o 31 x 10W LED power par
- o Super bright output, designed for auto show
- o Long distance throw
- o Video flicker free
- o HQ LEDs, long life time
- o Die-cast aluminum body
- o Available in tunable white or RGBW version



Scan for details

Strobe 1000 RGB

- o 200W RGB LED strobe
- o 1000 pcs SMD LEDs
- o Even color mixing, bright output
- o Strobe, Blinder, Wash all in one
- o Aluminum housing
- o Segment control



Scan for details

Strom 3000 RGBW

- o LED strobe light IP rated
- o Strobe, Blinder, Wash all in one
- o 1320pcs RGBW 4in1 LED
- o DMX, Auto, Sound control
- o 1-30 times/second strobe
- o Segment control



Scan for details

Pop Par 100 UV

- o 100W UV par light
- o 100° wide beam angle
- o Master-slave operation
- o Aluminum housing
- o Anti-corrosive coating
- o Overheat protection
- o RDM function



Scan for details

Spark C600

- o 600Watt cold spark machine
- o Light weight only 4.9kg
- o Safe, no gunpowder and smoke
- o DMX 512, remote control
- o Easy to setup and install
- o Aluminum housing
- o PowerCon in & out



Scan for details

Portable Power 1500

- o Portable power station 1500Watt
- o 1500Watt output
- o 24V 15AH
- o Portable, easy to carry and install
- o Intelligent and efficient fan cooling
- o Weight 8kgs
- o 1 - 1.5hours charging time



Scan for details

Portable Power 2000

- o Portable power station 2000Watt
- o 2000Watt output
- o 24V 32AH
- o Portable, easy to carry and install
- o Intelligent and efficient fan cooling
- o Weight 8kgs
- o 1 - 1.5hours charging time



Scan for details



RDM DMX SP8

- 8 optically isolated XLR(Neutrik) plugs for DMX output
- 2 Neutrik XLR (3-pin) for DMX input
- Variable data routing capabilities for all DMX outputs
- Serial connection possible
- LED indication for functions
- DMX Splitter / DMX booster operation possible
- DMX / RDM protocol...



Scan for details



ArtNet DMX AD8

- RJ45 Ethernet (LAN) interface, 10/100M/1000M self-adaptive, support TCP/IP protocol
- Network interface supports port auto-inversion (Auto MDI/MDIX)
- Support DMX-512 and ArtNet protocol, rdm protocol
- Support ArtNet to DMX signal bi-directional conversion
- DMX input / output can be enabled / disabled
- Each DMX output port can be set to single, zero, HTP, LTPRDM five modes...



Spacegun Spot 2035

- 10W white framing track
- 4 shuttuers for framing
- Camera lens style zoom
- 3000K, 4000K or 5600K
- High CRI of 95
- 25° - 30° zoom lens
- Black or white body



Showgun Spot 2035

- 10W/20W dual white framing track
- 4 shuttuers for framing
- Camera lens style zoom
- 2700K - 6000K CCT
- High CRI of 95
- 25° - 30° zoom lens
- Black or white body

New



Scan for details



Reborn 200C

- S4 LED retrofit RGBA
- RGBA color mixing
- 150Watt power
- 100 - 240V support
- XLR signal connection
- Easy to setup and install
- Flicker free



Showgun Spot 2540

- 30W dual white framing track
- 4 shuttuers for framing
- Camera lens style zoom
- 2700K - 6000K CCT
- High CRI of 95
- 25° - 40° zoom lens
- Black or white body



Showgun Spot 5060

- 35W dual white framing track
- 4 shuttuers for framing
- Camera lens style zoom
- 2700K - 6000K CCT
- High CRI of 95
- 50° - 60° zoom lens
- Black or white body



CTC 100 Profile

- 100W dual white profile spot
- 4 shuttuers for framing
- 2700K - 6500K CCT
- High CRI of 96
- 18° - 32° manual zoom
- Knob control
- Super compact size



CTC 100 Fresnel

- 100W dual white fresnel zoom
- 100W WW + 100W CW
- 2700K - 6500K CCT
- High CRI of 96
- 25° - 60° manual zoom
- Knob control
- Super compact size



Atmos 150C

- 150W RGBAL
- Downlight or fresnel light
- Fan free
- High CRI
- Fixed lens(degree optional)
- Powercon in



Reborn 200 Par

- Par light for Reborn 200
- Replacement for S4 par
- Single white or dual white
- High CRI
- Fixed angle
- Compact size

用心造好灯

Professional theatre, studio, gallery lights manufacture

Hotion[®]

Ovation[®]

ZVH[®]



Download latest catalog

Stay Social !



Instagram
[@ovationlight](#)



Twitter
[@ovationlight](#)



Facebook
[@ovationlighting](#)



Youtube

Guangzhou Hotion Technology Co., Ltd

Building 29, Meidong Industrial Park, Huadu District, Guangzhou, China (510880)

T: +86 020 86847336 | E: info@hotion.com | www.hotion.com

© Copyright by Hotion. All rights reserved.

All specifications are subject to change without prior notice V5.2